

Pointfix®

All Weather Epoxy Jointing Compound

Pointfix is a two part epoxy resin-based product offering far superior performance over conventional sand and cement mortar and polymeric jointing compounds.

This multi-purpose jointing and repair compound is available in 12kg and 20kg tubs. Each tub contains two bags, one bag contains the epoxy resin pigmented sand, and the second bag contains the hardener sand. Pointfix is easy to mix and measure compared to sand and cement mortar. The 1:1 mixing ratio means you only use the amount required from the packs, cutting down on waste.

Pointfix comes in a range of colours. Please see our Natural Shades colour range for even more colour choices.

How to apply Pointfix

First ensure the paving is clean and dust free

1. Mix the Pointfix packs A & B together thoroughly if a smaller amount is required mix in a 1:1 mixing ratio from each of the bags. We recommend using a round bucket mixing from the bottom up, ensure everything is mixed together all the way through thoroughly.
 2. Tip out small amounts over the joints and using a clean soft brush, brush the product across the joints diagonally.
- TIP.** Using the conventional pointing method along with adding water to the MIXED product will aid in the application.
3. Brush off any excess product with a soft clean brush, we recommend using a different brush from the one used for the initial application. Any residue left on the slabs should be removed using warm soapy water.
 4. Leave to cure for approximately 12-24 hours at 15-20°C. Note, curing times will be longer at lower temperatures and shorter at higher temperatures.

Using with porcelain

Pointfix is suitable for use with porcelain however like with all surfaces we recommend doing a small test area prior to use as some brands are more prone to staining than others. Wetting the paving before application along with adding water to the product after it has been mixed will significantly reduce the risk of left over residue.

Important; Please turn over for technical specifications

Whilst Pave Fix Limited endeavours to ensure that any advice recommendations specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification or information given.

Pointfix®

All Weather Epoxy Jointing Compound

Technical Specifications (Please read before mixing & applying)

- We aim to keep our colours consistent, but colours may vary between batches due to natural sand.
- Not suitable for all surfaces, we recommend doing a small test area prior to use.
- May cause staining on granite and some types of porcelain.
- Minimum joint width is 3mm. Minimum joint depth is 12mm (we recommend using the full depth of slab for maximum strength). Suitable for widths greater than 20mm.
- Do not apply when temperatures may fall below 0°C (we advise using when temperatures are 5°C or above).
- Do not apply when the surface temperature of the paving may exceed 35°C.
- Avoid unmixed product receiving prolonged exposure to high day time temperatures (we advise where possible storing the product in the shade prior to use).
- Always use clean tools and mixing bucket to avoid contamination.
- As with all chemical based compounds do not leave sitting on the slabs for a prolonged period of time.
- To applied in small amounts as close to the joints as possible and brushed in with a clean soft brush across the surface. Do not brush down into the slabs.
- Any residue must be cleaned off with hot soapy water before it has had time to cure.
- The finished product is weather resistant, fade resistant and chemical resistant.
- Shelf life of 24 months unopened when stored at room temperature and 12 months if opened providing the bags are folded up in the tub with the lid firmly on
- Multiple use (can be used to repair concrete floors, holes in walls etc).

Pointfix Coverage

20kg Tub

Paving Size/mm	Example 10mm Joint Width, 24mm deep
600 x 600	12.5m ²
600 x 450	10.5m ²
450 x 450	9m ²
300 x 450	7.5m ²
300 x 300	5.8m ²

12kg Tub

Paving Size/mm	Example 10mm Joint Width, 24mm deep
600 x 600	7.5m ²
600 x 450	6.3m ²
450 x 450	5.4m ²
300 x 450	4.5m ²
300 x 300	3.5m ²

All quoted coverages are approximates.

Health and Safety

Please see GHS sticker on the side of the tub which include H302, H315, H317, H318 and H412 warnings.

Pave Fix Ltd, 10 - 12 Stag Business Park, Christchurch Road, Ringwood, Hampshire, BH24 3AS

Website: www.pavefix.co.uk

Email: info@pavefix.co.uk

Telephone: 01425 478500